



## Azimut-KAMUT2L1

**Lyzard-KZ1** | Speakers

| General                           |                                      |
|-----------------------------------|--------------------------------------|
| Type                              | Point source                         |
| Transducers                       | 0.5" neodymium magnet woofer         |
| Frequency Response <sup>(1)</sup> | 500 Hz – 18 kHz (-6 dB)              |
| Max SPL <sup>(2)</sup>            | 86 dB (peak)                         |
| Rated Power                       | 3.5 W                                |
| Coverage                          | V. 140°   H. 140°                    |
| Connectors                        | IN+ IN- screw terminals              |
| Nominal Impedance                 | 16 Ω                                 |
| Handling & Finishes               |                                      |
| Dimensions (WxHxD)                | 22 x 37 x 11 mm (0.9 x 1.5 x 0.4 in) |
| Weight                            | 0.021 kg (0.046 lb)                  |
| Material                          | Aluminum                             |
| Colors                            | Black, White, Custom RAL             |
| Finishes                          | 24K Gold, Polished                   |
| IP Rating                         | IP64                                 |

**Truffle-KTR24** | Subwoofer

| General                           |   |
|-----------------------------------|---|
| Type                              | Passive subwoofer                       |
| Transducers                       | 4" woofer + passive radiator            |
| Frequency Response <sup>(1)</sup> | 45 Hz – 150 Hz (-6 dB)                  |
| Max SPL <sup>(2)</sup>            | 112 dB (peak)                           |
| Rated Power                       | 60 W                                    |
| Coverage                          | Omni                                    |
| Connectors                        | 2PIN euroblock connector (included)     |
| Nominal Impedance                 | 4 Ω                                     |
| Handling & Finishes               |   |
| Dimensions (WxHxD)                | 122 x 117 x 199 mm (4.8 x 4.6 x 7.8 in) |
| Weight                            | 1.5 kg (3.31 lb)                        |
| Material                          | Aluminum                                |
| Colors                            | Black                                   |
| Finishes                          | Powder Matte                            |
| IP Rating                         | IP64                                    |

**Kommander-KA02** | Amplifier

For technical specifications, see page 26



## Azimut-KAMUT2L14

**Lyzard-KZ14** | Speakers

| General                           |                                       |
|-----------------------------------|---------------------------------------|
| Type                              | Line array                            |
| Transducers                       | 4 x 0.5" neodymium magnet woofers     |
| Frequency Response <sup>(1)</sup> | 500 Hz – 18 kHz (-6 dB)               |
| Max SPL <sup>(3)</sup>            | 98 dB (peak)                          |
| Rated Power                       | 15 W                                  |
| Coverage                          | V. 40°   H. 140°                      |
| Connectors                        | IN+ IN- screw terminals               |
| Nominal Impedance                 | 16 Ω                                  |
| Handling & Finishes               |                                       |
| Dimensions (WxHxD)                | 22 x 100 x 11 mm (0.9 x 3.9 x 0.4 in) |
| Weight                            | 0.059 kg (0.130 lb)                   |
| Material                          | Aluminum                              |
| Colors                            | Black, White, Custom RAL              |
| Finishes                          | 24K Gold, Polished                    |
| IP Rating                         | IP64                                  |

**Truffle-KTR25** | Subwoofer

| General                           |  |
|-----------------------------------|--|
| Type                              | Passive subwoofer                        |
| Transducers                       | 5.25" woofer + passive radiator          |
| Frequency Response <sup>(1)</sup> | 45 Hz – 150 Hz (-6 dB)                   |
| Max SPL <sup>(2)</sup>            | 115 dB (peak)                            |
| Rated Power                       | 80 W                                     |
| Coverage                          | Omni                                     |
| Connectors                        | 2PIN euroblock connector (included)      |
| Nominal Impedance                 | 4 Ω                                      |
| Handling & Finishes               |  |
| Dimensions (WxHxD)                | 152 x 147 x 258 mm (6.0 x 5.8 x 10.2 in) |
| Weight                            | 2.5 kg (5.51 lb)                         |
| Material                          | Aluminum                                 |
| Colors                            | Black                                    |
| Finishes                          | Powder Matte                             |
| IP Rating                         | IP64                                     |

**Kommander-KA02** | Amplifier

For technical specifications, see page 26



## Azimut-KAMUT2L

**Lyzard-KZ14** | Speakers

| General                |                                       |
|------------------------|---------------------------------------|
| Type                   | Line array                            |
| Transducers            | 4 x 0.5" neodymium magnet woofers     |
| Frequency Response (1) | 500 Hz – 18 kHz (-6 dB)               |
| Max SPL (3)            | 98 dB (peak)                          |
| Rated Power            | 15 W                                  |
| Coverage               | V. 40°   H. 140°                      |
| Connectors             | IN+ IN- screw terminals               |
| Nominal Impedance      | 16 Ω                                  |
| Handling & Finishes    |                                       |
| Dimensions (WxHxD)     | 22 x 100 x 11 mm (0.9 x 3.9 x 0.4 in) |
| Weight                 | 0.059 kg (0.130 lb)                   |
| Material               | Aluminum                              |
| Colors                 | Black, White, Custom RAL              |
| Finishes               | 24K Gold, Polished                    |
| IP Rating              | IP64                                  |

**Rumble-KU44** | Subwoofer

| General                           |  |
|-----------------------------------|--|
| Type                              | Passive subwoofer  |
| Transducers                       | 2 x 4" neodymium magnet woofers<br>2 x 4" passive radiator |
| Frequency Response <sup>(1)</sup> | 50 Hz – 150 Hz (-6 dB)                                     |
| Max SPL <sup>(2)</sup>            | 116 dB (peak)  |
| Rated Power                       | 120 W  |
| Coverage                          | Omni   |
| Connectors                        | 4PIN euroblock connector (included)                        |
| Nominal Impedance                 | 2 Ω  |
| Handling & Finishes               |  |
| Dimensions (WxHxD) <sup>(1)</sup> | 500 x 116 x 100 mm (19.7 x 4.6 x 4.0 in)                   |
| Weight                            | 5.9 kg (13.0 lb)   |
| Material                          | Stainless Steel  |
| Colors                            | Black, White, Custom RAL                                   |
| Finishes                          | Gold, Polished, Brushed                                    |
| IP Rating <sup>(7)</sup>          | IP64   |

**Kommander-KA02** | Amplifier

For technical specifications, see page 26