Domino

Full-range, compact stainless steel speakers



Restaurants and Cafes

() m

Hotels and Resorts



Theme Parks



Museums and Exhibitions



General

Type Transducers

Frequency Response (1) Max SPL (2) Rated Power Coverage Connectors Nominal Impedance

Handling & Finishes

Dimensions (WxHxD) (11) Weight Material Colors Finishes IP Rating

Domino-KF26

Point source

6" neodymium magnet woofer 2" neodymium magnet woofer 6" passive transducer

50 Hz - 19 kHz (-6 dB) 115 dB (peak) 160 W

V. 90° | H. 90°

IP64 (8)

4PIN euroblock connector (included) 8Ω/32Ω

180 x 350 x 118 mm (7.1 x 13.8 x 4.6 in) 6.5 kg (14.3 lb) Stainless Steel Black, White, Custom RAL 24K Gold, Polished, Brushed

Point source

10" neodymium magnet woofer 3" neodymium magnet woofer 10" passive transducer

40 Hz - 19 kHz (-6 dB) 123 dB (peak)

320 W V. 90° | H. 90°

4PIN euroblock connector (included)

4 Ω / 16 Ω

IP64 (8)

282 x 500 x 151 mm (11.1 x 19.7 x 5.9 in) 12 kg (26.5 lb)

Stainless Steel Black, White, Custom RAL 24K Gold, Polished, Brushed

8Ω

IP43 (6)

Point source

Coax. 12" woofer 1,7" compression driver 12" passive transducer 40 Hz - 19 kHz (-6 dB) 130 dB (peak)

700 W V. 60° | H. 90° 4PIN euroblock connector (included)

330 x 655 x 200 mm (13.0 x 25.8 x 7.9 in) 23.5 kg (51.8 lb)

Stainless Steel Black, White, Custom RAL 24K Gold, Polished, Brushed

