



Truffle

Extremely compact and easily
concealable aluminum alloy subwoofers



Restaurants and Cafes



Hotels and Resorts



Fitness and Wellness



Retail



Museums and Exhibitions



Boardrooms and Conference Rooms



General

Type	Passive subwoofer
Transducers	4" woofer + passive radiator
Frequency Response ⁽¹⁾	45 Hz – 150 Hz (-6 dB)
Max SPL ⁽²⁾	112 dB (peak)
Rated Power	60 W
Coverage	Omni
Connectors	2PIN euroblock connector (included)
Nominal Impedance	4 Ω

Handling & Finishes

Dimensions (WxHxD)	122 x 117 x 199 mm (4.8 x 4.6 x 7.8 in)
Weight	1.5 kg (3.31 lb)
Material	Aluminum
Colors	Black
Finishes	Powder Matte
IP Rating	IP64

Truffle-KTR24

Type	Passive subwoofer
Transducers	4" woofer + passive radiator
Frequency Response ⁽¹⁾	45 Hz – 150 Hz (-6 dB)
Max SPL ⁽²⁾	112 dB (peak)
Rated Power	60 W
Coverage	Omni
Connectors	2PIN euroblock connector (included)
Nominal Impedance	4 Ω

Dimensions (WxHxD)	122 x 117 x 199 mm (4.8 x 4.6 x 7.8 in)
Weight	1.5 kg (3.31 lb)
Material	Aluminum
Colors	Black
Finishes	Powder Matte
IP Rating	IP64

Truffle-KTR25

Type	Passive subwoofer
Transducers	5.25" woofer + passive radiator
Frequency Response ⁽¹⁾	45 Hz – 150 Hz (-6 dB)
Max SPL ⁽²⁾	115 dB (peak)
Rated Power	80 W
Coverage	Omni
Connectors	2PIN euroblock connector (included)
Nominal Impedance	4 Ω

Dimensions (WxHxD)	152 x 147 x 258 mm (6.0 x 5.8 x 10.2 in)
Weight	2.5 kg (5.51 lb)
Material	Aluminum
Colors	Black
Finishes	Powder Matte
IP Rating	IP64

Truffle-KTR26

Type	Passive subwoofer
Transducers	6.5" woofer + passive radiator
Frequency Response ⁽¹⁾	45 Hz – 150 Hz (-6 dB)
Max SPL ⁽²⁾	120 dB (peak)
Rated Power	100 W
Coverage	Omni
Connectors	2PIN euroblock connector (included)
Nominal Impedance	2 Ω

Dimensions (WxHxD)	182 x 176 x 341 mm (7.1 x 6.9 x 13.4 in)
Weight	3.5 kg (7.72 lb)
Material	Aluminum
Colors	Black
Finishes	Powder Matte
IP Rating	IP64

