

PS/PAS 6"/8" WALL MOUNT

IS outdoor series

PS6/8

6"/8" full range passive speaker

PAS6/8

6"/8" full range active speaker



available in BLACK or WHITE

IS8TW

8" 100V line full range outdoor speaker



alternative colours available

ISG1T

100V line omnidirectional garden speaker



alternative colours available

hard wearing moulded cabinet design

available in black or white

wall mounting brackets included

active and passive versions

free standing or wall mounted

2-way system for full coverage

8" full range indoor / outdoor speaker

coated aluminium construction

IP rated for outdoor brackets included

clear omnidirectional garden speaker

coated aluminium for durability

IP rating and UV protection

	PS-6	PS-8		PAS-6	PAS-8
MAX SPL PEAK	112dB	115dB	MAX SPL	112dB	115dB
PGM	120W	160W	AMP PEAK	240W	320W
RMS	60W	80W	AMP PGM	120W	160W
WEIGHT	4kg	5kg	AMP RMS	60W	80W
Cabinet type	6.5" 2-way passive	8" 2-way passive	WEIGHT	4kg	5kg
Frequency response	80Hz - 20kHz	60Hz - 20kHz	Cabinet type	6.5" 2-way active	8" 2-way active
Sensitivity 1w@1m	91dB	93dB	Frequency response	80Hz - 20kHz	60Hz - 20kHz
Nominal Impedance	8 ohm	8 ohm	Sensitivity 1w@1m	-15dBu	-15dBu
LF Driver	1 x 6.5" driver	1 x 8" driver	LF Driver	1 x 6.5" driver	1 x 8" driver
HF Driver	1 x dome tweeter	1 x dome tweeter	HF Driver	1 x dome tweeter	1 x dome tweeter
Crossover frequency	3kHz	3kHz	Crossover frequency	3kHz	3kHz
Input connection	Jack	Jack	EQ	2 band	2 band
Dimensions (wxhxd)	230 x 360 x 220mm	280 x 410 x 250mm	Input connection	Jack in, amp out	Jack in, amp out
			Dimensions (wxhxd)	230 x 360 x 220mm	280 x 410 x 250mm

	IS8TW		ISG1T
MAX SPL PEAK	106dB	MAX SPL	102dB
PGM	60W	PEAK	120W
RMS	30W	PGM	60W
WEIGHT	8.5kg	RMS	30W
Cabinet type	8" 70/100V weatherproof	WEIGHT	6kg
Cabinet material	Coated aluminium	Cabinet type	2-way 70/100V weatherproof
Frequency response	100Hz - 20kHz	Cabinet material	Coated aluminium
Sensitivity 1w@1m	91dB	Frequency response	80Hz - 10kHz
Nominal Impedance	70/100V line	Sensitivity 1w@1m	88dB
LF Driver	8" driver	Nominal Impedance	70/100V line
HF Driver	compression driver	LF Driver	6.5" driver
Dimensions (wxhxd)	230 x 250 x 430mm	HF Driver	3" driver
		Dimensions (dia x h)	240 x 440mm