



ANALOGUE CONSOLES

C2/C2S ultra compact

C2/C2S series



C2-2 2 MIC - 2 STEREO

- 2 mic input and 2 stereo input channels
- Comprehensive channel facilities including 2 band EQ and auxiliary
- Ultra compact lightweight design



C2S-2 2 MIC - 2 STEREO WITH USB

- 2 mic input and 2 stereo input channels
- Comprehensive channel facilities including 2 band EQ and auxiliary
- Ultra compact lightweight design
- Built in USB record / playback



C2-4 4 MIC - 2 STEREO

- 4 mic input and 2 stereo input channels
- Comprehensive channel facilities including 2 band EQ and auxiliary
- Ultra compact lightweight design



C2S-4 4 MIC - 2 STEREO WITH USB

- 4 mic input and 2 stereo input channels
- Comprehensive channel facilities including 2 band EQ and auxiliary
- Ultra compact lightweight design
- Built in USB record / playback



4 models - 2 or 4 mic input with/without USB interface **ultra compact design**
2-band EQ on all channels **USB interface for playback/record** **auxiliary output**
balanced inputs and outputs **multiple applications** **external power supply**

| SPECIFICATIONS | C2-2 | C2S-2 | C2-4 | C2S-4 |
|--------------------|---|---|---|---|
| Channels | 6 | 6 | 8 | 8 |
| Mic Inputs | 2 | 2 | 4 | 4 |
| Stereo Inputs | 4 | 4 | 4 | 4 |
| Frequency Response | 20Hz-20kHz (+/-1dB) | 20Hz-20kHz (+/-1dB) | 20Hz-20kHz (+/-1dB) | 20Hz-20kHz (+/-1dB) |
| Distortion | <0.08% @ -10dBu | <0.08% @ -10dBu | <0.08% @ -10dBu | <0.08% @ -10dBu |
| Residual Noise | <-98dB | <-98dB | <-98dB | <-98dB |
| Gain Range | Mic Input: 0dB to +45dB Line Input: -20dB to +25dB | Mic Input: 0dB to +45dB Line Input: -20dB to +25dB | Mic Input: 0dB to +45dB Line Input: -20dB to +25dB | Mic Input: 0dB to +45dB Line Input: -20dB to +25dB |
| Input Impedance | Line: 20k ohm balanced Playback+ CDMP3: 24k ohm unbalanced | Line: 20k ohm balanced 24k ohm unbalanced | Line: 20k ohm balanced 24k ohm unbalanced | Line: 20k ohm balanced 24k ohm unbalanced |
| EQ | Hi: +/-15dB @ 12kHz Lo: +/-15dB @ 80Hz | +/-15dB @ 12kHz +/-15dB @ 80Hz | +/-15dB @ 12kHz +/-15dB @ 80Hz | +/-15dB @ 12kHz +/-15dB @ 80Hz |
| Maximum Output | Main Mix: +21dB +/-2dB Aux Send: +18dB +/-2B | +21dB +/-2dB +18dB +/-2B | +21dB +/-2dB +18dB +/-2B | +21dB +/-2dB +18dB +/-2B |
| Output Impedance | Record: 1k ohm Headphones: 25k ohm | 1k ohm 25k ohm | 1k ohm 25k ohm | 1k ohm 25k ohm |
| USB | N/A | 2 channel playback/record | N/A | 2 channel playback/record |
| Dimensions (WxHxD) | 165 x 75 x 244mm | 165 x 75 x 244mm | 218 x 75 x 244mm | 218 x 75 x 244mm |
| Power Supply | Wall adaptor 100-240V ~ 50/60Hz | Wall adaptor 100-240V ~ 50/60Hz | Wall adaptor 100-240V ~ 50/60Hz | Wall adaptor 100-240V ~ 50/60Hz |
| Power Consumption | 11W | 11W | 15W | 15W |